



FIELDKING TIPPING TRAILER



BENEFITS:

- Flexibility of loading/unloading goods/ materials like farm produce by simply tipping them saves overall operating cost of transportation.
- World class hub, axle, bearings & tipping mechanism enhances life (durability & reliability).

FEATURES:

- Front door fixed by nuts & bolts. Drop down side doors for easy loading /unloading & bottom opening Rear door (All doors removable).
- Easily transportable as it gets easily attached/ mounted.
- Well designed for towing and loading stability.

SPECIFICATIONS:

SR.NO	DESCRIPTION	FKAT4WT-5T	FKAT4WT-9T	FKAT4WT-12T
1	Outer Dimensions	10'x6'x1.75' Feet (3048x1828x534 mm)	12'x6'x2Feet (3658x1828x610 mm)	14'x7'x2Feet (4270x1828x610 mm)
2	Main Chassis	150x75 mm	150x75 mm	150x75 mm
3	Floor Sheet	4 mm	4 mm	4 mm
4	Side Wall Sheet	2 mm (Corrugated)	2 mm (Corrugated)	2 mm (Corrugated)
5	Tyres	4 nos. of 7.5x16	2 nos. of 7.5x16 2 nos. of 9.00 x16	12.5/80-15.3 both pairs.
6	Hitch Beam	75x40 mm	100x50 mm	100x50 mm
7	Hydraulic Cylinder capacity	10 ton	15 ton	20 ton
8	Ring Hitch	50 mm dia.	50 mm dia.	50 mm dia.
9	Axle	75 mm Square (Front & Rear)	75 mm Square (Front & Rear)	75 mm Square(Front) 90 mm Square(Rear)
10	Axle Bearing (SKF)	32214 inner and 32213	32214 inner and 32213	32216 inner and 32213
11	Weight	1700 Kg (Approx.)	1880 Kg (Approx.)	2150 Kg (Approx.)
12	Tractor Power HP	50-70	70-90	90-110

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com